Mighty Lite Erector Series continued...

16'

MIGHTY LITE® ERECTOR SERIES PANEL SELECTION APPROXIMATE DIGGING DEPTH (FT.) & SOIL TYPE					H (FT.)		
MODEL	HEIGHT	LENGTH	WEIGHT	A	В	(C
				25	45	60	80
MLES-22	2'	2'	30#	124	71	54	32
MLES-23	2'	3'	42#	112	64	49	29
MLES-24	2'	4'	53#	100	57	44	26
MLES-25	2'	5'	65#	96	55	42	25
MLES-26	2'	6'	77#	92	53	41	24
MLES-27	2'	7'	90#	72	42	32	19
MLES-28	2'	8'	102#	52	31	24	14
MLES-210	2'	10'	125#	36	22	17	11
MLES-212	2'	12'	150#	28	17	14	9
MLES-214	2'	14'	175#	20	13	11	7

OTHER SIZES ON REQUEST


14

10

CUSTOM

All panels have tongue and groove construction. Solid bottom cutting edges are available as well as full length top protectors.

198#



MLES-216

2 WAY "T" CORNER END POSTS

MODEL	HEIGHT	WEIGHT	
		(EACH)	
ECP-2	2'	18#	
ECP-4	4'	35#	
ECP-6	6'	52#	
ECP-8	8'	68#	
ECP-10	10'	85#	



3 WAY "T" CORNER END POSTS

MODEL	HEIGHT	WEIGHT
		(EACH)
TECP-2	2'	30#
TECP-4	4'	50#
TECP-6	6'	70#
TECP-8	8'	90#
TECP-10	10'	110#
TECP-12	12'	130#



4 WAY CORNER END POSTS

MODEL	HEIGHT	WEIGHT
		(EACH)
4ECP-2	2'	35#
4ECP-4	4'	70#
4ECP-6	6'	90#
4ECP-8	8'	135#
4ECP-10	10'	170#
4ECP-12	12'	205#

SPREADER SELECTIONS



Adjustable NiCad plated screw jacks

SCREW JACK SELECTION

Includes Pins & Keepers

MODEL	WIDTH	WEIGHT
		(EACH)
ESJ-23	24" - 36"	25#
ESJ-35	36" -60"	38#
ESJ-57	60" - 84"	42#
ESJ-79	84" - 108"	49#

Other sizes available by request.
Threaded portion of jacks are NiCad plated to resist corrosion.
Each strut is held in place with
(4) 5/8" pins & keepers.



ADJUSTABLE SQUARE STEEL BOX TUBING SPREADERS

MODEL	WIDTH	WEIGHT		
		(EACH)		
AST-1824	18"- 24"	30#		
AST-2436	24"- 36"	35#		
AST-3660	36"- 60"	52#		
AST-4872	48"- 72"	68#		
AST-6096	60"- 96"	82#		
AST-72108	72"-108"	95#		
AST-84120	84"-120"	115#		
AST-84120	96"-144"	130#		

OTHER SIZES ON REQUEST Each strut is held in place with (4) 5/8" diameter pins with keepers.



MODEL	WIDTH	WEIGHT	
		(EACH)	
ESJ-23-SS	24" - 36"	25#	
ESJ-35-SS	36" -60"	38#	
ESJ-57-SS	60" - 84"	42#	
ESJ-79-SS	84" - 108"	49#	

Other sizes available by request. Each strut is held in place with (4) 5/8" pins & keepers.